


LAMP PHOTOMETRIC REPORT

MODEL: 93DFLD6030/BL		
POWER: 60W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 5746.9 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	5413	6275	6691	5631	5135	5733	6723	6391	0- 10	596.9	596.9	10.4
20	3795	4998	6085	4454	3666	4530	6180	5122	10- 20	1526	2122	36.9
30	2245	3553	4011	3244	2159	3362	4127	3712	20- 30	1897	4020	69.9
40	230.7	1497	1335	1025	209.7	1066	1435	1697	30- 40	1275	5294	92.1
50	56.16	162.0	253.6	100.4	51.93	104.9	266.0	199.1	40- 50	364.2	5659	98.5
60	18.45	28.07	50.46	20.84	17.12	21.68	51.50	30.41	50- 60	70.49	5729	99.7
70	4.267	5.822	7.394	3.854	3.265	4.026	7.722	5.935	60- 70	15.97	5745	100
80	0.2561	0.3883	0.4262	0.3199	0.2909	0.3162	0.3661	0.3159	70- 80	1.583	5747	100
90	0.1939	0.2226	0.3005	0.2475	0.2936	0.3488	0.3933	0.3200	80- 90	0.3223	5747	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 30 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

