

Floodlight Summary:

Report based on lamp delivering 1000 lumens.

Maximum Intensity	2630.9 cd per klm.
(Luminaire orientation as tested.)	0.0 degrees vertical
	0.0 degrees horizontal

Beam Spread	At 10% of Imax	51.9V x 51.2H
	At 50% of Imax	28.5V x 28.4H
	At 90% of Imax	12.0V x 12.4H

Beam Flux	Total	739.4 lumens per klm.
	To 10% of Imax	637.5 lumens per klm.
	To 50% of Imax	380.0 lumens per klm.
	To 90% of Imax	88.7 lumens per klm.

Upward LOR	0.0 %
Downward LOR	73.9 %


Luminaire Efficiency (Light Output Ratio)	73.7 %
---	--------

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 29 August 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

LUMINAIRE PHOTOMETRIC TEST REPORT

NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:



DATA OF LAMP		PHOTOMETRIC DATA	
MODEL	93SS1040/BL	Imax (cd)	2105
NOMINAL POWER (W)	10	AVAILABILITY (%)	63.5
RATED VOLTAGE (V)	230	Avai. FLUX (lm)	508.3
NOMINAL FLUX (lm)	800	LOR (%)	73.7
LAMPS INSIDE	1	TOTAL FLUX (lm)	589.5
TEST VOLTAGE (V)	230	θ @50% (H,V)	28,28DEG

VERTICAL (DEG)	AREA FLUX DIAGRAM																UNIT:lm		Φ t	Φ a
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00
90	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.04	0.00
80	0.00	0.00	0.00	0.00	0.02	0.03	0.03	0.02	0.02	0.02	0.02	0.02	0.01	0.01	0.00	0.00	0.00	0.00	0.20	0.00
70	0.00	0.00	0.00	0.01	0.02	0.03	0.04	0.06	0.06	0.06	0.05	0.04	0.02	0.02	0.01	0.00	0.00	0.00	0.43	0.00
60	0.00	0.00	0.01	0.02	0.03	0.06	0.13	0.26	0.37	0.37	0.28	0.15	0.06	0.03	0.01	0.00	0.00	0.00	1.78	0.00
50	0.00	0.00	0.01	0.02	0.05	0.17	0.48	0.99	1.42	1.48	1.08	0.54	0.19	0.05	0.02	0.01	0.00	0.00	6.51	0.00
40	0.00	0.00	0.01	0.03	0.10	0.43	1.39	3.59	6.34	6.66	4.02	1.58	0.50	0.12	0.03	0.01	0.00	0.00	24.8	9.91
30	0.00	0.00	0.01	0.03	0.17	0.84	3.37	11.0	24.3	25.7	12.6	3.96	0.96	0.20	0.03	0.01	0.00	0.00	83.1	74.2
20	0.00	0.00	0.01	0.04	0.24	1.25	5.64	23.0	51.2	53.0	26.7	6.67	1.46	0.27	0.04	0.01	0.00	0.00	169	162
10	0.00	0.00	0.02	0.04	0.24	1.30	5.85	23.7	52.2	54.4	27.5	6.86	1.47	0.28	0.05	0.01	0.00	0.00	174	166
0	0.00	0.00	0.01	0.04	0.18	0.92	3.73	12.1	26.7	28.0	13.7	4.22	1.00	0.22	0.04	0.01	0.00	0.00	90.9	82.2
-10	0.00	0.00	0.01	0.03	0.11	0.49	1.58	4.14	7.34	7.58	4.46	1.71	0.53	0.13	0.03	0.01	0.00	0.00	28.2	13.5
-20	0.00	0.00	0.01	0.02	0.05	0.19	0.56	1.11	1.60	1.63	1.15	0.59	0.21	0.06	0.02	0.01	0.00	0.00	7.22	0.00
-30	0.00	0.00	0.01	0.02	0.03	0.06	0.15	0.31	0.44	0.43	0.30	0.17	0.07	0.03	0.01	0.00	0.00	0.00	2.04	0.00
-40	0.00	0.00	0.00	0.01	0.02	0.03	0.05	0.07	0.09	0.09	0.07	0.05	0.03	0.02	0.01	0.00	0.00	0.00	0.53	0.00
-50	0.00	0.00	0.00	0.00	0.01	0.01	0.02	0.03	0.03	0.03	0.03	0.02	0.02	0.01	0.00	0.00	0.00	0.00	0.23	0.00
-60	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.01	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.06	0.00
-70	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-80	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
HORIZONTAL (DEG)																				
Φ t	0.00	0.02	0.12	0.31	1.27	5.82	23.0	80.4	172	179	92.0	26.6	6.55	1.44	0.31	0.08	0.01	0.00	590	---
Φ a	0.00	0.00	0.00	0.00	0.00	0.00	8.26	70.7	164	171	82.5	12.2	0.00	0.00	0.00	0.00	0.00	0.00	---	508

one-half-peak spread: U:14.7,D:13.9 , L:13.7,R:14.9


NEMA Beam Type: Type 4

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:29 August 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature: 25.3°C
Operators:
Test Date: 29 August 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.265m [K=1.0000]
Remarks:

ISOLUX DIAGRAM


NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 29 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

Planar Illuminance Curve




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 29 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

AAI Figure

NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:



Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: HIGH
 Temperature: 25.3°C
 Operators:
 Test Date: 29 August 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.265m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:

Table--1

UNIT: cd

H(DEC) V(DEC)	-90	-85	-80	-75	-70	-65	-60	-55	-50	-45	-40	-35	-30	-25	-20	-15	-10	-5	0
-90	0.02	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
-85	0.02	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.01	0.01	0.00	0.01	0.01	0.01	0.00	0.01	0.02	0.01	0.00
-80	0.02	0.01	0.00	0.00	0.01	0.01	0.00	0.01	0.02	0.02	0.00	0.02	0.04	0.03	0.02	0.03	0.05	0.04	0.02
-75	0.02	0.01	0.00	0.01	0.02	0.01	0.00	0.02	0.04	0.04	0.04	0.05	0.08	0.09	0.10	0.12	0.14	0.18	0.21
-70	0.02	0.01	0.00	0.01	0.02	0.02	0.02	0.04	0.07	0.09	0.12	0.24	0.41	0.51	0.57	0.68	0.79	0.88	0.96
-65	0.02	0.01	0.00	0.01	0.03	0.04	0.05	0.08	0.20	0.35	0.44	0.55	0.73	0.87	0.94	1.02	1.08	1.12	1.14
-60	0.02	0.01	0.00	0.01	0.04	0.06	0.10	0.31	0.46	0.58	0.72	0.86	1.05	1.19	1.29	1.38	1.43	1.45	1.44
-55	0.02	0.01	0.00	0.01	0.05	0.10	0.35	0.52	0.69	0.86	1.02	1.15	1.35	1.62	1.88	2.16	2.37	2.53	2.63
-50	0.02	0.01	0.00	0.02	0.06	0.25	0.56	0.72	0.92	1.13	1.30	1.51	1.90	2.46	3.13	4.29	5.05	5.68	6.18
-45	0.02	0.01	0.01	0.02	0.09	0.54	0.70	0.91	1.15	1.38	1.62	2.15	3.11	5.05	7.50	10.2	12.4	13.8	14.1
-40	0.02	0.01	0.01	0.03	0.15	0.66	0.85	1.09	1.37	1.69	2.29	3.86	6.63	10.1	14.6	19.7	24.7	27.5	27.6
-35	0.02	0.01	0.01	0.04	0.40	0.76	0.97	1.27	1.60	2.24	3.81	6.92	11.8	18.7	27.6	34.8	42.7	47.3	49.0
-30	0.02	0.01	0.01	0.06	0.65	0.85	1.08	1.42	1.94	2.98	6.37	11.4	22.4	33.5	47.2	66.3	87.6	105	114
-25	0.02	0.01	0.02	0.07	0.79	0.92	1.21	1.59	2.34	4.48	9.20	18.2	33.2	52.6	85.9	132	192	232	255
-20	0.02	0.01	0.02	0.08	0.86	0.99	1.32	1.76	2.70	6.19	12.6	26.3	47.9	82.8	149	238	339	441	491
-15	0.02	0.01	0.02	0.09	0.92	1.03	1.40	2.02	3.40	7.78	16.1	34.3	65.8	130	230	386	625	890	1008
-10	0.02	0.01	0.02	0.10	0.99	1.07	1.43	2.16	3.96	9.03	20.2	42.0	85.7	168	313	594	1041	1424	1605
-5	0.02	0.02	0.02	0.10	1.04	1.09	1.43	2.21	4.22	9.80	23.0	47.0	101	202	385	795	1371	1799	1988
0	0.02	0.02	0.02	0.11	1.10	1.10	1.41	2.20	4.24	10.1	24.3	47.3	105	210	407	875	1493	1944	2105
5	0.02	0.02	0.03	0.11	1.05	1.06	1.39	2.09	4.10	9.66	23.2	44.1	96.5	192	371	774	1338	1777	1950
10	0.02	0.02	0.03	0.11	1.00	1.03	1.34	1.92	3.74	8.65	20.2	38.4	79.9	159	293	547	976	1357	1517
15	0.02	0.02	0.03	0.10	0.95	0.98	1.28	1.73	3.18	7.20	15.2	30.5	59.2	113	209	350	556	795	908
20	0.02	0.02	0.03	0.10	0.89	0.93	1.19	1.50	2.56	5.72	11.5	23.7	42.1	74.6	130	211	301	389	431
25	0.02	0.02	0.03	0.09	0.83	0.89	1.09	1.37	2.15	4.07	8.50	15.6	28.2	46.8	74.5	114	160	202	221
30	0.02	0.02	0.03	0.08	0.72	0.87	0.98	1.23	1.72	2.84	5.78	10.2	17.9	29.0	43.2	59.5	75.0	89.2	92.7
35	0.02	0.02	0.03	0.07	0.46	0.85	0.91	1.09	1.36	2.08	3.56	6.39	10.3	15.9	24.7	32.2	38.0	42.7	44.6
40	0.02	0.02	0.03	0.07	0.17	0.83	0.88	0.98	1.19	1.50	2.30	3.63	5.88	8.68	11.9	16.1	20.9	24.6	26.5
45	0.02	0.02	0.03	0.06	0.10	0.78	0.86	0.92	1.02	1.22	1.53	2.25	3.06	4.35	6.33	8.40	9.98	10.9	11.3
50	0.02	0.02	0.03	0.05	0.07	0.32	0.84	0.89	0.95	1.03	1.20	1.48	1.90	2.31	2.67	3.52	4.16	4.37	4.19
55	0.02	0.02	0.03	0.04	0.05	0.08	0.59	0.86	0.98	1.00	1.04	1.16	1.28	1.40	1.54	1.75	1.83	1.85	1.82
60	0.02	0.02	0.03	0.03	0.03	0.05	0.10	0.62	1.01	1.11	1.11	1.07	1.03	1.05	1.09	1.13	1.13	1.12	1.10
65	0.02	0.02	0.02	0.02	0.02	0.03	0.06	0.09	0.38	1.06	1.16	1.12	1.00	0.89	0.83	0.81	0.81	0.80	0.77
70	0.02	0.02	0.02	0.02	0.02	0.03	0.04	0.05	0.05	0.08	0.19	0.60	0.85	0.86	0.76	0.71	0.68	0.55	0.42
75	0.02	0.02	0.02	0.02	0.01	0.02	0.04	0.03	0.03	0.04	0.06	0.06	0.05	0.07	0.09	0.09	0.07	0.09	0.10
80	0.02	0.02	0.02	0.02	0.01	0.02	0.03	0.02	0.01	0.02	0.04	0.03	0.02	0.03	0.05	0.03	0.02	0.04	0.05
85	0.02	0.02	0.02	0.02	0.01	0.02	0.02	0.02	0.01	0.02	0.02	0.02	0.01	0.02	0.03	0.02	0.01	0.02	0.03
90	0.02	0.01	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.02

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:29 August 2022

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

NAME: 93SS1040/BL	TYPE: 93SS1040/BL	WEIGHT: 1
SPEC.:	DIM.: 40 x 75 x 40	SERIAL No.: 0
MFR.: Elmark Industries JSC	SUR.: circle	Shielding Angle:

Table--2

UNIT: cd

H (DEG) V (DEG)	5	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	
-90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
-85	0.01	0.02	0.01	0.00	0.01	0.02	0.01	0.00	0.01	0.02	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.00	
-80	0.04	0.05	0.04	0.02	0.03	0.04	0.02	0.01	0.02	0.03	0.01	0.00	0.01	0.01	0.01	0.00	0.00	0.00	
-75	0.22	0.22	0.25	0.24	0.16	0.10	0.06	0.04	0.04	0.04	0.02	0.00	0.01	0.02	0.01	0.00	0.01	0.00	
-70	0.92	0.88	0.86	0.83	0.76	0.66	0.47	0.26	0.13	0.07	0.04	0.02	0.02	0.02	0.01	0.00	0.01	0.00	
-65	1.09	1.03	0.98	0.92	0.87	0.81	0.75	0.65	0.51	0.23	0.09	0.05	0.04	0.03	0.01	0.00	0.01	0.00	
-60	1.44	1.41	1.35	1.26	1.16	1.05	0.92	0.79	0.62	0.46	0.26	0.10	0.06	0.04	0.01	0.00	0.01	0.00	
-55	2.65	2.55	2.33	2.01	1.71	1.39	1.21	1.03	0.84	0.63	0.41	0.25	0.10	0.05	0.01	0.01	0.01	0.00	
-50	5.81	5.20	4.45	3.50	2.93	2.36	1.77	1.33	1.09	0.84	0.60	0.39	0.19	0.06	0.02	0.01	0.01	0.00	
-45	13.3	11.7	9.59	7.69	5.59	3.71	2.77	1.93	1.35	1.07	0.79	0.52	0.31	0.09	0.02	0.01	0.01	0.00	
-40	26.2	23.4	19.4	16.0	11.1	7.36	4.64	2.88	1.92	1.28	0.97	0.67	0.39	0.12	0.03	0.01	0.01	0.00	
-35	47.6	43.9	35.4	28.6	20.4	12.6	7.81	4.64	2.68	1.65	1.15	0.79	0.46	0.20	0.04	0.02	0.01	0.00	
-30	107	92.2	73.0	49.5	34.2	21.9	12.3	7.30	3.60	2.13	1.31	0.91	0.55	0.27	0.06	0.02	0.01	0.00	
-25	239	203	142	91.1	57.0	34.7	19.5	10.7	5.48	2.65	1.53	1.03	0.63	0.32	0.07	0.03	0.01	0.00	
-20	464	366	261	167	94.9	50.1	28.3	14.9	7.64	3.14	1.74	1.13	0.69	0.36	0.09	0.03	0.02	0.00	
-15	935	704	434	257	147	74.5	35.5	18.8	9.64	4.10	2.02	1.21	0.75	0.39	0.10	0.03	0.02	0.00	
-10	1496	1150	701	363	194	100.0	44.7	22.4	11.3	4.92	2.21	1.28	0.78	0.41	0.11	0.04	0.02	0.00	
-5	1885	1514	946	458	234	118	51.5	24.3	11.9	5.26	2.31	1.32	0.81	0.43	0.12	0.04	0.02	0.00	
0	2004	1630	1025	485	246	123	54.0	24.7	11.8	5.23	2.33	1.34	0.82	0.43	0.13	0.04	0.02	0.00	
5	1824	1464	918	442	225	114	50.7	24.0	11.2	4.96	2.21	1.30	0.81	0.43	0.12	0.04	0.02	0.00	
10	1420	1090	648	344	194	95.1	44.2	21.2	9.98	4.39	2.02	1.24	0.78	0.41	0.12	0.04	0.02	0.00	
15	847	629	400	240	133	69.2	35.0	16.8	8.59	3.65	1.77	1.15	0.75	0.39	0.11	0.04	0.02	0.00	
20	411	331	235	155	85.6	48.3	26.9	13.3	6.94	2.83	1.50	1.05	0.70	0.36	0.10	0.04	0.02	0.00	
25	213	177	131	85.0	52.6	33.1	18.8	9.83	4.95	2.35	1.36	0.95	0.64	0.32	0.09	0.04	0.02	0.00	
30	91.3	79.9	63.3	45.6	31.7	20.9	11.7	6.57	3.11	1.82	1.20	0.86	0.55	0.28	0.08	0.04	0.02	0.00	
35	45.2	41.0	34.1	27.0	18.1	11.7	7.09	3.93	2.21	1.39	1.04	0.75	0.44	0.21	0.07	0.04	0.02	0.00	
40	26.7	23.7	19.6	15.2	10.3	6.87	3.97	2.34	1.51	1.16	0.90	0.64	0.36	0.13	0.06	0.03	0.02	0.00	
45	10.7	9.96	8.69	6.94	4.97	3.00	2.11	1.49	1.18	0.98	0.76	0.48	0.28	0.09	0.05	0.03	0.02	0.00	
50	4.16	3.90	3.34	2.59	2.12	1.66	1.32	1.12	0.94	0.79	0.58	0.36	0.16	0.06	0.04	0.03	0.02	0.00	
55	1.79	1.70	1.56	1.34	1.21	1.11	0.99	0.86	0.72	0.56	0.41	0.24	0.08	0.04	0.04	0.03	0.02	0.00	
60	1.08	1.06	1.04	0.98	0.88	0.81	0.73	0.61	0.46	0.36	0.26	0.10	0.05	0.03	0.03	0.02	0.02	0.00	
65	0.76	0.73	0.71	0.67	0.59	0.50	0.41	0.35	0.29	0.16	0.09	0.06	0.03	0.02	0.02	0.02	0.01	0.00	
70	0.39	0.36	0.36	0.34	0.29	0.24	0.19	0.12	0.08	0.05	0.05	0.04	0.02	0.02	0.02	0.02	0.01	0.00	
75	0.09	0.07	0.09	0.09	0.07	0.05	0.06	0.06	0.03	0.02	0.03	0.03	0.02	0.01	0.02	0.02	0.01	0.00	
80	0.04	0.02	0.04	0.05	0.03	0.02	0.03	0.03	0.02	0.01	0.02	0.02	0.02	0.01	0.02	0.02	0.01	0.00	
85	0.02	0.01	0.02	0.03	0.02	0.01	0.02	0.02	0.02	0.01	0.01	0.02	0.01	0.01	0.02	0.02	0.01	0.00	
90	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.01	0.01	0.02	0.01	0.01	0.01	0.01	0.01	0.00	

C Range: 0 - 360DEG

C Interval: 10.0DEG

Test Speed: HIGH

Temperature:25.3°C

Operators:

Test Date:29 August 2022

γ Range: 0 - 90DEG

γ Interval: 2.5DEG

Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456

Humidity:65.0%

Test Distance:6.265m [K=1.0000]

Remarks: