



LUMINAIRE PHOTOMETRIC TEST REPORT

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |

| DATA OF LAMP | | PHOTOMETRIC DATA | | | |
|-------------------|------------------|------------------|--------|--------------------------|-----------|
| MODEL | 95SHELLY18LED/GR | Imax (cd) | 979.5 | S/MH (C0/180) | 1.28 |
| NOMINAL POWER (W) | 18 | LOR (%) | 132.8 | S/MH (C90/270) | 1.27 |
| RATED VOLTAGE (V) | 230 | TOTAL FLUX (lm) | 2869.2 | η UP, DN (C0-180) | 0.0, 66.6 |
| NOMINAL FLUX (lm) | 2160 | CIE CLASS | DIRECT | η UP, DN (C180-360) | 0.0, 66.2 |
| LAMPS INSIDE | 1 | η up (%) | 0.0 | CIBSE SHR NOM | 1.25 |
| TEST VOLTAGE (V) | 230 | η down (%) | 132.8 | CIBSE SHR MAX | 1.35 |



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

| γ | C0 | C45 | C90 | C135 | C180 | C225 | C270 | C315 | γ | Φ zone | Φ total | %lum, lamp |
|----------|-----------------------|-------|-------|-------|-------|-------|-------|-------|----------|-------------|--------------|------------|
| 10 | 960.8 | 961.0 | 962.7 | 966.1 | 966.4 | 965.3 | 963.1 | 959.9 | 0- 10 | 92.68 | 92.68 | 3.23,4.29 |
| 20 | 909.5 | 911.9 | 916.1 | 921.2 | 921.2 | 919.0 | 914.9 | 909.2 | 10- 20 | 266.2 | 358.9 | 12.5,16.6 |
| 30 | 830.0 | 832.6 | 837.3 | 844.5 | 844.4 | 842.7 | 835.7 | 828.3 | 20- 30 | 405.5 | 764.4 | 26.6,35.4 |
| 40 | 721.8 | 725.3 | 730.4 | 738.8 | 738.4 | 736.4 | 729.1 | 719.7 | 30- 40 | 492.1 | 1257 | 43.8,58.2 |
| 50 | 589.6 | 593.4 | 598.2 | 606.7 | 606.1 | 604.6 | 596.7 | 586.5 | 40- 50 | 514.1 | 1771 | 61.7,82 |
| 60 | 437.2 | 440.8 | 445.1 | 453.6 | 452.7 | 451.4 | 443.8 | 433.3 | 50- 60 | 467.6 | 2238 | 78,104 |
| 70 | 273.4 | 276.8 | 280.0 | 288.1 | 286.6 | 286.2 | 279.2 | 268.8 | 60- 70 | 359.0 | 2597 | 90.5,120 |
| 80 | 118.8 | 119.5 | 121.5 | 127.6 | 126.6 | 126.5 | 121.1 | 112.5 | 70- 80 | 210.0 | 2807 | 97.8,130 |
| 90 | 2.241 | 2.218 | 2.608 | 4.672 | 3.429 | 3.705 | 3.146 | 2.206 | 80- 90 | 61.90 | 2869 | 100,133 |
| 100 | | | | | | | | | 90-100 | | | |
| 110 | | | | | | | | | 100-110 | | | |
| 120 | | | | | | | | | 110-120 | | | |
| 130 | | | | | | | | | 120-130 | | | |
| 140 | | | | | | | | | 130-140 | | | |
| 150 | | | | | | | | | 140-150 | | | |
| 160 | | | | | | | | | 150-160 | | | |
| 170 | | | | | | | | | 160-170 | | | |
| 180 | | | | | | | | | 170-180 | | | |
| DEG | LUMINOUS INTENSITY:cd | | | | | | | | | UNIT:lm | | |

Conical surface Flux(90deg): 1515.1 lm

%lum = 52.8%

%lamp = 70.1%

Conical surface Flux(130deg): 2434.6 lm

%lum = 84.9%


%lamp = 112.7%

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.340m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |



| LUMINANCE cd/(m2) | | |
|-------------------|--------|---------|
| G (DEG) | C0/180 | C90/270 |
| 85 | 5149 | 5385 |
| 80 | 6046 | 6170 |
| 75 | 6562 | 6754 |
| 70 | 7062 | 7218 |
| 65 | 7438 | 7578 |
| 60 | 7725 | 7849 |
| 55 | 7941 | 8059 |
| 50 | 8104 | 8206 |
| 45 | 8231 | 8322 |

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

WEC AND CCEC

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |

| pcc | 80% | | | 70% | | | 50% | | | 30% | | | 10% | | | 0 |
|------|-----------------------|------|------|------|------|------|---------------------------------|------|------|------|------|------|------|------|------|---|
| pw | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0 |
| pfc | 20% | | | 20% | | | 20% | | | 20% | | | 20% | | | 0 |
| RCR | RCR:Room Cavity Ratio | | | | | | Wall Exitance Coefficients(WEC) | | | | | | | | | |
| 0.0 | | | | | | | | | | | | | | | | |
| 1.0 | .419 | .238 | .075 | .409 | .233 | .074 | .392 | .225 | .072 | .375 | .216 | .069 | .360 | .209 | .067 | |
| 2.0 | .392 | .215 | .066 | .384 | .212 | .065 | .369 | .205 | .064 | .354 | .199 | .062 | .341 | .193 | .061 | |
| 3.0 | .362 | .193 | .058 | .355 | .190 | .057 | .341 | .185 | .056 | .328 | .180 | .055 | .317 | .175 | .054 | |
| 4.0 | .334 | .174 | .051 | .327 | .171 | .051 | .315 | .167 | .050 | .304 | .163 | .049 | .293 | .159 | .049 | |
| 5.0 | .308 | .157 | .046 | .303 | .155 | .045 | .292 | .152 | .045 | .282 | .149 | .044 | .272 | .145 | .044 | |
| 6.0 | .286 | .143 | .041 | .281 | .142 | .041 | .271 | .139 | .040 | .262 | .136 | .040 | .253 | .133 | .040 | |
| 7.0 | .266 | .131 | .037 | .261 | .130 | .037 | .253 | .128 | .037 | .244 | .125 | .036 | .237 | .123 | .036 | |
| 8.0 | .248 | .121 | .034 | .244 | .120 | .034 | .236 | .118 | .034 | .229 | .116 | .033 | .222 | .114 | .033 | |
| 9.0 | .232 | .112 | .031 | .229 | .111 | .031 | .222 | .110 | .031 | .215 | .108 | .031 | .209 | .106 | .031 | |
| 10.0 | .218 | .105 | .029 | .215 | .104 | .029 | .209 | .102 | .029 | .203 | .101 | .029 | .197 | .099 | .028 | |

| pcc | 80% | | | 70% | | | 50% | | | 30% | | | 10% | | | 0 |
|------|-----------------------|------|------|------|------|------|---|------|------|------|------|------|------|------|------|---|
| pw | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 50% | 30% | 10% | 0 |
| ρfc | 20% | | | 20% | | | 20% | | | 20% | | | 20% | | | 0 |
| RCR | RCR:Room Cavity Ratio | | | | | | Ceiling Cavity Exitance Coefficients (CCEC) | | | | | | | | | |
| 0.0 | .253 | .253 | .253 | .216 | .216 | .216 | .148 | .148 | .148 | .085 | .085 | .085 | .027 | .027 | .027 | |
| 1.0 | .240 | .207 | .178 | .205 | .178 | .153 | .140 | .122 | .106 | .081 | .071 | .062 | .026 | .023 | .020 | |
| 2.0 | .229 | .175 | .130 | .197 | .151 | .112 | .135 | .104 | .078 | .078 | .061 | .046 | .025 | .020 | .015 | |
| 3.0 | .219 | .152 | .098 | .188 | .131 | .085 | .129 | .091 | .060 | .075 | .053 | .035 | .024 | .017 | .012 | |
| 4.0 | .209 | .134 | .077 | .179 | .116 | .067 | .123 | .081 | .047 | .071 | .047 | .028 | .023 | .015 | .009 | |
| 5.0 | .199 | .120 | .062 | .171 | .104 | .054 | .118 | .073 | .038 | .068 | .043 | .023 | .022 | .014 | .007 | |
| 6.0 | .190 | .109 | .052 | .163 | .095 | .045 | .112 | .066 | .032 | .065 | .039 | .019 | .021 | .013 | .006 | |
| 7.0 | .180 | .100 | .044 | .155 | .087 | .038 | .107 | .061 | .027 | .062 | .036 | .016 | .020 | .012 | .005 | |
| 8.0 | .172 | .092 | .038 | .148 | .080 | .033 | .102 | .056 | .023 | .060 | .033 | .014 | .019 | .011 | .005 | |
| 9.0 | .164 | .086 | .033 | .141 | .075 | .029 | .098 | .052 | .021 | .057 | .031 | .012 | .018 | .010 | .004 | |
| 10.0 | .156 | .080 | .030 | .135 | .070 | .026 | .093 | .049 | .018 | .054 | .029 | .011 | .018 | .010 | .004 | |

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

| | | | | | | | | | | | |
|---|--------|------------------|------|------|----------------|------|----------------|------------------|------|------|------|
| NAME: 95SHELLY18LED/GR | | | | | TYPE: | | | WEIGHT: 1 | | | |
| SPEC.: | | | | | DIM.: 400 x 60 | | | SERIAL No.: 0 | | | |
| MFR.: Elmark Industries JSC | | | | | SUR.: cilinder | | | Shielding Angle: | | | |
| ceiling/cavity | 0.7 | 0.7 | 0.5 | 0.5 | 0.3 | 0.7 | 0.7 | 0.5 | 0.5 | 0.3 | |
| walls | 0.5 | 0.3 | 0.5 | 0.3 | 0.3 | 0.5 | 0.3 | 0.5 | 0.3 | 0.3 | |
| working plane | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | |
| Room dimensions | | Viewed crosswise | | | | | Viewed endwise | | | | |
| x = 2H | y = 2H | 17.4 | 18.9 | 17.7 | 19.1 | 19.3 | 17.4 | 19.0 | 17.7 | 19.2 | 19.4 |
| | 3H | 18.9 | 20.3 | 19.2 | 20.6 | 20.8 | 19.0 | 20.4 | 19.3 | 20.6 | 20.9 |
| | 4H | 19.5 | 20.9 | 19.8 | 21.1 | 21.4 | 19.6 | 21.0 | 19.9 | 21.2 | 21.5 |
| | 6H | 20.0 | 21.2 | 20.3 | 21.5 | 21.8 | 20.1 | 21.3 | 20.4 | 21.6 | 21.9 |
| | 8H | 20.1 | 21.3 | 20.4 | 21.6 | 21.9 | 20.2 | 21.4 | 20.5 | 21.7 | 22.0 |
| | 12H | 20.2 | 21.4 | 20.5 | 21.7 | 22.0 | 20.3 | 21.5 | 20.6 | 21.8 | 22.1 |
| 4H | 2H | 18.0 | 19.4 | 18.3 | 19.6 | 19.9 | 18.0 | 19.4 | 18.4 | 19.7 | 19.9 |
| | 3H | 19.7 | 20.9 | 20.1 | 21.2 | 21.5 | 19.8 | 21.0 | 20.1 | 21.3 | 21.6 |
| | 4H | 20.5 | 21.5 | 20.8 | 21.9 | 22.2 | 20.5 | 21.6 | 20.9 | 21.9 | 22.3 |
| | 6H | 21.0 | 22.0 | 21.4 | 22.3 | 22.7 | 21.1 | 22.1 | 21.5 | 22.4 | 22.8 |
| | 8H | 21.2 | 22.1 | 21.6 | 22.5 | 22.9 | 21.3 | 22.2 | 21.7 | 22.6 | 23.0 |
| | 12H | 21.3 | 22.2 | 21.8 | 22.6 | 23.0 | 21.4 | 22.3 | 21.9 | 22.6 | 23.0 |
| 8H | 4H | 20.7 | 21.6 | 21.1 | 22.0 | 22.4 | 20.8 | 21.7 | 21.2 | 22.1 | 22.4 |
| | 6H | 21.5 | 22.2 | 21.9 | 22.6 | 23.0 | 21.5 | 22.3 | 22.0 | 22.7 | 23.1 |
| | 8H | 21.7 | 22.4 | 22.2 | 22.8 | 23.3 | 21.8 | 22.5 | 22.3 | 22.9 | 23.3 |
| | 12H | 21.9 | 22.5 | 22.4 | 23.0 | 23.4 | 22.0 | 22.6 | 22.5 | 23.0 | 23.5 |
| 12H | 4H | 20.7 | 21.6 | 21.2 | 22.0 | 22.4 | 20.8 | 21.6 | 21.2 | 22.0 | 22.4 |
| | 6H | 21.5 | 22.2 | 22.0 | 22.6 | 23.1 | 21.6 | 22.2 | 22.0 | 22.7 | 23.1 |
| | 8H | 21.8 | 22.4 | 22.3 | 22.9 | 23.3 | 21.9 | 22.5 | 22.4 | 22.9 | 23.4 |
| Variations with the observer position at spacings(CIE Pub.117): | | | | | | | | | | | |
| S = 1.0H | | + 0.1 / - 0.2 | | | | | + 0.1 / - 0.2 | | | | |
| 1.5H | | + 0.2 / - 0.3 | | | | | + 0.2 / - 0.3 | | | | |
| 2.0H | | + 0.2 / - 0.3 | | | | | + 0.2 / - 0.3 | | | | |

CIE Pub.117, 2160 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 2.7)
Area: 0.113354 m2

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |


| REFLECTANCE | | | | | | | | | | |
|----------------------------------|--|-----|-----|-----------|-----|-----|-----|---------------|-----|--------|
| Ceiling | 0.8 | 0.8 | 0.8 | 0.7 | 0.7 | 0.7 | 0.5 | 0.5 | 0.5 | 0 |
| Walls | 0.7 | 0.5 | 0.3 | 0.7 | 0.5 | 0.3 | 0.7 | 0.5 | 0.3 | 0 |
| Working plane | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0.2 | 0 |
| ROOM INDEX | UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$ | | | | | | | | | |
| $k = 0.60$ | 76 | 60 | 51 | 75 | 60 | 51 | 73 | 59 | 51 | 42 |
| 0.80 | 89 | 74 | 64 | 88 | 73 | 63 | 85 | 72 | 63 | 54 |
| 1.00 | 100 | 85 | 76 | 99 | 85 | 75 | 96 | 87 | 74 | 65 |
| 1.25 | 110 | 96 | 86 | 108 | 95 | 85 | 104 | 93 | 84 | 75 |
| 1.50 | 116 | 103 | 94 | 114 | 102 | 93 | 110 | 100 | 92 | 82 |
| 2.00 | 126 | 114 | 105 | 123 | 112 | 104 | 118 | 110 | 102 | 92 |
| 2.50 | 131 | 120 | 112 | 128 | 119 | 111 | 123 | 115 | 109 | 97 |
| 3.00 | 135 | 126 | 119 | 133 | 124 | 117 | 127 | 120 | 114 | 103 |
| 4.00 | 141 | 133 | 127 | 138 | 131 | 125 | 132 | 126 | 121 | 110 |
| 5.00 | 144 | 138 | 132 | 141 | 135 | 130 | 135 | 130 | 126 | 114 |
| ROOM INDEX | UF(total) | | | | | | | | | Direct |
| According to DIN EN 13032-2 2004 | | | | Suspended | | | | SHRNOM = 1.25 | | |

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |




C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature:25.3°C
 Operators:
 Test Date:19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity:65.0%
 Test Distance:6.340m [K=1.0000]
 Remarks:

AAI Figure

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |



C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature: 25.3°C
Operators:
Test Date: 19 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity: 65.0%
Test Distance: 6.340m [K=1.0000]
Remarks:

LED Avg.L Report

| | | |
|-----------------------------|----------------|------------------|
| NAME: 95SHELLY18LED/GR | TYPE: | WEIGHT: 1 |
| SPEC.: | DIM.: 400 x 60 | SERIAL No.: 0 |
| MFR.: Elmark Industries JSC | SUR.: cilinder | Shielding Angle: |


| AvgL | cd/m2 |
|------------------|-------|
| L_0~180 (65) av | 7582 |
| L_0~180 (75) av | 6755 |
| L_0~180 (85) av | 5494 |
| L_90~270 (65) av | 7570 |
| L_90~270 (75) av | 6745 |
| L_90~270 (85) av | 5444 |
| L_45 (65) av | 7581 |
| L_45 (75) av | 6754 |
| L_45 (85) av | 5473 |

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:19 January 2023

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
 C Interval: 10.0DEG
 Test Speed: MEDIUM
 Temperature: 25.3°C
 Operators:
 Test Date: 19 January 2023

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
 Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.456
 Humidity: 65.0%
 Test Distance: 6.340m [K=1.0000]
 Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.340m [K=1.0000]
Remarks:

```