


LAMP PHOTOMETRIC REPORT

MODEL: 98Vega30Slim/WH		
POWER: 30W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 2110.0 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	766.0	766.6	770.8	770.9	776.2	771.3	771.7	767.4	0- 10	73.95	73.95	3.5
20	728.4	734.6	739.3	738.7	749.4	739.7	741.4	736.0	10- 20	213.7	287.6	13.6
30	668.2	674.8	683.3	687.9	699.9	691.4	687.1	677.6	20- 30	328.9	616.5	29.2
40	582.4	591.5	602.9	613.4	621.9	617.9	608.0	594.9	30- 40	404.1	1021	48.4
50	453.7	481.5	446.3	508.7	511.5	515.5	446.2	486.5	40- 50	419.9	1441	68.3
60	302.1	297.7	284.7	326.6	348.3	330.4	294.8	303.5	50- 60	353.2	1794	85
70	145.0	138.1	120.0	144.6	195.0	153.4	129.3	144.9	60- 70	228.4	2022	95.8
80	9.746	25.89	8.151	25.40	28.54	30.49	15.24	30.32	70- 80	83.05	2105	99.8
90	0.8765	0	0	0	0.8779	0	0	0	80- 90	4.867	2110	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3°C
Operators:
Test Date:05 July 2022

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:
```